

MARKING SYSTEM

HTM-TTR

SumiTag Thermal Transfer Ribbon 2020 Super Premium Ribbon for printing on polyolefin heat-shrink tubing and labels



Highlights

- Designed for printing on polyolefin shrink tubing
- Superior resistance to solvents and scratches
- Can be used in extreme environments
- High resolution printing

- Wide range of printable products
- Various widths available
- Standards: MIL-STD-202F Method 215J; SAE-AS81531

iTAG-Reference	Length mm	Width mm	Series	Colour	Rolls/Box
HTM-TTR-100-300-BK-2020	300	100	2020	black	1
HTM-TTR-080-300-BK-2020	300	80	2020	black	1
HTM-TTR-060-300-BK-2020	300	60	2020	black	1
HTM-TTR-040-300-BK-2020	300	40	2020	black	1

Technical characteristics

Ribbon storage conditions	

Heat Resistance	5 °C - 35 °C	
Chemicals	10% bis 85% relative humidity	
Light Shelf life	Avoid direct sunlight 36 months from manufacture	
Recommendation	Product stored at 20 °C and 50% relative humidit unopened	

Created by: NH 03042020

RELIABLE, FLEXIBLE, CUSTOMER-ORIENTED

HEINRICH THULESIUS GMBH & CO. KG Zum Panrepel 15, D-28307 Bremen, GERMANY



We reserve the right to make product changes.

SERVICE Tel: +49 (0) 421-4895-0 Fax: +49 (0) 421-4895-225 E-Mail: info@thulesius.de www.thulesius.de

SUMITOMO ELECTRIC GROUP