

## CABLE TIES

### HTQ-HR

QuickLok-Kabelbinder, Heat Resistant



#### Highlights

- Temperature range  
- 40 °C up to 85 °C
- High tensile strength
- Zero halogen
- Pre-curved tongue for easy assembly
- Self-extinguishing
- Excellent resistance against many chemicals
- Weatherproof in black
- Approval: UL94-V2

#### Dimension

Art.-No. natural	Art.-No. black	Reference *	Cable Tie (mm)		Bundle Diameter mm / Max.	Loop Tensile Strength min. kg	Pcs./ Unit	Pcs./ Box
			Length	Width				
Z80900	Z80700	HTQ-HR-100	98	2.50	21	8.16	100	15.000
Z80920	Z80XXX	HTQ-HR-140	140	3.60	32	18.34	100	7.000
Z80921	Z80XXX	HTQ-HR-200/1	200	3.60	50	18.34	100	7.000
Z80946	Z80XXX	HTQ-HR-200/2	200	4.80	50	22.44	100	10.000
Z80925	Z80XXX	HTQ-HR-290	290	4.80	78	22.44	100	3.500
Z80XXX	Z80XXX	HTQ-HR-365	365	7.50	100	55.08	100	1.500

\* HR = Heat Resistant

Standard colours: natural, black

#### Technical characteristics

Property	Test	Inspection requirements
Material	Polyamid 6.6, heat stabilized, natural and black halogenfree	
Thermal	Operating temperature Installation temperature	-40 °C - 125 °C -10 °C - 60 °C
Chemical	Flammability Water absorption	UL94-V2, self-extinguishing Flammability class: V2 2.7% (50% relative humidity)

Created by: NH 03042020

We reserve the right to make product changes.

**RELIABLE, FLEXIBLE,  
CUSTOMER-ORIENTED**

**HEINRICH THULESIUS GMBH & CO. KG**  
Zum Panrepel 15, D-28307 Bremen, GERMANY



#### SERVICE

Tel: +49 (0) 421-48 95-0  
Fax: +49 (0) 421-48 95-225  
E-Mail: [info@thulesius.de](mailto:info@thulesius.de)  
[www.thulesius.de](http://www.thulesius.de)